

# STANDARD SELF-CONTAINED HOPPER LOADER

## FEATURE:

- With small footprint and low weight, available of being placed directly onto other machines or containers for auto loading.
- Microcomputer controller.
- Alarm for overload and lack of material.
- 300G equipped with high-speed rectifier motor with delicate size and strong suction force-suitable for new materials.
- 400G with Induction high pressure pump - with low noise and long service time.
- Cable control board design—easy to set and control with distance.
- Filter for air and dust (Optional part).



**YT-X300G**

## SPECIFICATIONS

Model		YT-X300G	YT-X400G
Motor	Type	Carbon Brush	Induction
	Specification	1.1KW/1.3HP 1Φ	0.75KW/1HP 3Φ
Conveying Capacity ( KG/H )		300	330
Loading Distance ( M )		3.5	4
Static Wind Pressure ( MM/H2O )		1300	1400
Reservoir Volume ( L )		7.5	7.5
Conveying Tube Inner Diameter ( MM )		Φ38	Φ38
Specification of the Attached Hosess ( MM )		38mm x 3.5m 1Pcs	Φ38mmx4m 1Pcs
Dimension. L*W*H ( CM )		34 x 34 x 59	45 x 37 x 66
Approx. Net Weight ( KG )		12	27

Conveying capacity and loading distance are tested by ABS material; actual data may differ by plastic proportions, shapes, loading lengths and heights, pipe conditions and parameter settings.

For processing hot materials, Heat-Resistant(160°C) pipes are necessary.



**YT-X400G**

Note: We reserve the right to cancel or change the above specific model without any prior notice.